



06A-01



06A-02



06A-03



06A-03G

Name	ESD SMT Magazine Rack	
Model	06A-01	
Surface Resistance	10 ⁵ -10 ⁸ Ω	
Dimension	460*400*563mm	
PCB Storage Qty	50PCS	
PCB Size	460*(50-330)mm	
Directive Ditch of Side Plate	Depth:3.5mm Width:5mm Spacing:10mm	
Adjust Method	Screw adjustment fixed type	
Top and bottom boards Material	Metal	

Name	ESD SMT Magazine Rack	
Model	06A-02	
Surface Resistance	10 ⁵ -10 ⁸ Ω	
Dimension	355*315*580mm	
PCB Storage Qty	51PCS	
PCB Size	355*(80-250)mm	
Directive Ditch of Side Plate	Depth:3.2mm Width:7mm Spacing:10mm	
Adjust Method	Screw adjustment fixed type	
Top and bottom boards Material	ESD Plastic	

Name	ESD SMT Magazine Rack	
Model	06A-03	06A-03G
Temp Resistance	Normal	130℃
Surface Resistance	10 ⁵ -10 ⁸ Ω	
Dimension	355*320*563mm	
PCB Storage Qty	50PCS	
PCB Size	355*(50-250)mm	
Directive Ditch of Side Plate	Depth:3mm Width:5.5mm Spacing:10mm	
Adjust Method	Gear and wheel structure to change distance	
Top and bottom boards Material	Metal	



06A-04



06A-04G



06A-05

Name	ESD SMT Magazine Rack		
Model	06A-04	06A-04G	06A-05
Temp Resistance	Normal	130°C	Normal
Surface Resistance	10 ⁵ -10 ⁸ Ω		
Dimension	355*320*563mm		
PCB Storage Qty	50PCS		
PCB Size	355*(50-250)mm		
Directive Ditch of Side Plate	Depth:3mm Width:5.5mm Spacing:10mm		
Adjust Method	Screw adjustment fixed type		Gear and wheel
Top and bottom boards Material	Metal		ESD Plastic



06A-06



06A-06G



06A-07



06A-07G

Name	ESD SMT Magazine Rack			
Model	06A-06	06A-06G	06A-07	06A-07G
Temp Resistance	Normal	130℃	Normal	130℃
Surface Resistance	10^5-10^8 Ω			
Dimension	460*400*563mm			
PCB Storage Qty	50PCS			
PCB Size	460*(50-330)mm			
Directive Ditch of Side Plate	Depth:4mm Width:5.5mm Spacing:10mm			
Adjust Method	Gear and wheel structure to change distance		Screw adjustment fixed type	
Top and bottom boards Material	Metal			



06A-04S



06A-08



06A-09

Name	ESD SMT Magazine Rack
Model	06A-04S
Surface Resistance	10^5 - $10^8 \Omega$
Dimension	355*320*563mm
PCB Storage Qty	100PCS
PCB Size	355*(50-225 , 75-225)mm
Directive Ditch of Side Plate	Depth:3mm Width:5.5mm Spacing:10mm
Adjust Method	Screw adjustment fixed type
Top and bottom boards Material	Metal

Name	ESD SMT Magazine Rack
Model	06A-08
Surface Resistance	10^5 - $10^8 \Omega$
Dimension	535*460*570mm
PCB Storage Qty	50PCS
PCB Size	535*(50-390)mm
Directive Ditch of Side Plate	Depth:4mm Width:5.5mm Spacing:10mm
Adjust Method	Gear and wheel structure to change distance
Top and bottom boards Material	Metal

Name	ESD SMT Magazine Rack
Model	06A-09
Surface Resistance	10^5 - $10^8 \Omega$
Dimension	535*530*570mm
PCB Storage Qty	50PCS
PCB Size	535*(120-460)mm
Directive Ditch of Side Plate	Depth:4mm Width:5.5mm Spacing:10mm
Adjust Method	Gear and wheel structure to change distance
Top and bottom boards Material	Metal



1	355mm side board, Temp Resistance 230°C
2	355mm side board
3	460mm side board
4	535mm side board
5	Short Rotating lever
6	Long Rotating lever
7	Barrier lever
8	Square column
9	Base board middle handle
10	Bow connector
11	Rack (small)
12	Adapter (left)
13	Adapter (right)
14	Gear

We support customize special size ,if need ,please contact us .Thanks!

Attached for reference only.

外形尺寸: 355*315*580mm		温度℃		存放PCB尺寸		槽型尺寸			插槽数量	基础尺寸		上下面板		齿轮压扣	螺丝固定	重量 kg
产品型号	特点	槽板	环境	插槽长度	可调节宽度mm	槽宽	槽深	间距		A	B	金属	塑料			
A-02	整体侧板	100	70	355	80-250	7.2	4.3	10	50	34	34	-	√	-	√	
A02T	金属底板	100	100	355	80-250	7.2	4.3	10	50	34	34	√	-	-	√	

外形尺寸: 355*320*563mm		温度℃		存放PCB尺寸		槽型尺寸			插槽数量	基础尺寸		上下面板		齿轮压扣	螺丝固定	重量 kg
产品型号	特点	槽板	环境	插槽长度	可调节宽度mm	槽宽	槽深	间距		A	B	金属	塑料			
A-03	五拼板	120	60	355	35-250	5	3.4	10	50	34	34	√	-	√	-	
A-03R	底板1.2厚	120	60	355	35-250	5	3.4	10	50	34	34	√	-	√	-	
A-03G	耐高温侧板	230	60	355	35-250	5	3.4	10	50	34	34	√	-	√	-	
A-03ZT	整体侧板	120	60	355	35-250	7.3	3.2	10	50	34	34	√	-	√	-	
A03J215	槽宽15mm	120	60	355	35-250	15	3.4	20	50	34	34	√	-	√	-	
A03J205	槽宽5mm	120	60	355	35-250	5	3.4	20	50	34	34	√	-	√	-	
A-03LG	铝合金侧板	520	60	355	35-250	8	3	10	50	34	34	√	-	√	-	
A-03SL5	不锈钢底板	120	60	355	35-250	5	3.4	10	50	34	34	√	-	√	-	
A-04	五拼板	120	120	355	35-250	5	3.4	10	50	34	34	√	-	-	√	
A-04G	整体耐高温	230	230	355	35-250	5	3.4	10	50	34	34	√	-	-	√	6.5
A-04S	中间加双面板	120	100	355	35-250	5	3.4	10	100	34	34	√	-	-	√	
A-04J20	槽宽15mm	120	100	355	35-250	15	3.4	20	50	34	34	√	-	-	√	
A-04LG	铝合金侧板	520	520	355	35-250	8	3	10	50	34	34	√	-	-	√	
A-05	塑料底板	120	60	355	35-250	5	3.4	10	50	34	34	-	√	√	-	
A-05ZT	整体侧板	120	60	355	35-250	7.3	3.2	10	50	34	34	-	√	√	-	
A05J20	槽宽15mm	120	60	355	35-250	15	3.4	20	50	34	34	-	√	√	-	
A-03PD	同步皮带	80	60	342	40-250	5	3	10	50	34	34	√	-	√	-	
A-03LT	链条同步	120	120	355	50-250	5	3.4	10	50	34	34	-	√	-	金属链条	

外形尺寸: 355*320*263mm 355*320*363mm (小料架)		温度℃		存放PCB尺寸		槽型尺寸			插槽数量	基础尺寸		上下面板		齿轮压扣	螺丝固定	重量 kg
产品型号	特点	槽板	环境	插槽长度	可调节宽度mm	槽宽	槽深	间距		A	B	金属	塑料			
A-03X2	存放20层	120	60	355	35-250	5	3.4	10	20	34	34	√	-	√	-	
A-03X3	存放30层	120	60	355	35-250	5	3.4	10	30	34	34	√	-	√	-	
A-03LGX2	铝合金20层	520	60	355	35-250	8	3	10	20	34	34	√	-	√	-	
A-03LGX3	铝合金30层	520	60	355	35-250	8	3	10	30	34	34	√	-	√	-	
A-04X2	存放20层	120	100	355	35-250	5	3.4	10	20	34	34	√	-	-	√	
A-04X3	存放30层	120	100	355	35-250	5	3.4	10	30	34	34	√	-	-	√	
A-04LGX2	铝合金20层	520	520	355	35-250	8	3	10	20	34	34	√	-	-	√	
A-04LGX3	铝合金30层	520	520	355	35-250	8	3	10	30	34	34	√	-	-	√	
A-05X2	存放20层	120	60	355	35-250	5	3.4	10	20	34	34	-	√	√	-	
A-05X3	存放30层	120	60	355	35-250	5	3.4	10	30	34	34	-	√	√	-	

外形尺寸: 400*320*563mm 400*380*563mm		温度℃		存放PCB尺寸		槽型尺寸			插槽数量	基础尺寸		上下面板		齿轮压扣	螺丝固定	重量 kg
产品型号	特点	槽板	环境	插槽长度	可调节宽度mm	槽宽	槽深	间距		A	B	金属	塑料			
A-4032	400系列	120	60	400	35-250	5	3	10	50	34	34	√	-	√	-	
A-4038	400系列	120	60	400	35-310	5	3	10	50	34	34	√	-	√	-	

外形尺寸: 460*400*563mm		温度℃		存放PCB尺寸		槽型尺寸			插槽数量	基础尺寸		上下面板		齿轮压扣	螺丝固定	重量 kg
产品型号	特点	槽板	环境	插槽长度	可调节宽度mm	槽宽	槽深	间距		A	B	金属	塑料			
A-06-2	老款二插槽	120	60	460	35-330	5	3.4	10	50	34	34	√	-	√	-	8.2
A-06-3	新款三插槽	120	60	460	35-330	5	3.4	10	50	34	34	√	-	√	-	
A-06G	三插槽耐高温	230	60	460	35-330	5	3.4	10	50	34	34	√	-	√	-	10.1
A-06LG	铝合金侧板	520	60	460	35-330	8	3	10	50	34	34	√	-	√	-	10.4
A-07-2	老款二插槽	120	100	460	35-330	5	3.4	10	50	34	34	√	-	-	√	
A-07-3	新款三插槽	120	100	460	35-330	5	3.4	10	50	34	34	√	-	-	√	
A-07G	整体耐高温	230	230	460	35-330	5	3.4	10	50	34	34	√	-	-	√	
A-07S	中间加双面板	120	100	460	35-330	5	3.4	10	100	34	34	√	-	-	√	
A-07LG	铝合金侧板	520	520	460	35-330	8	3	10	50	34	34	√	-	-	√	

外形尺寸: 460*400*263mm 460*400*363mm (小料架)		温度℃		存放PCB尺寸		槽型尺寸			插槽数量	基础尺寸		上下面板		齿轮压扣	螺丝固定	重量 kg
产品型号	特点	槽板	环境	插槽长度	可调节宽度mm	槽宽	槽深	间距		A	B	金属	塑料			
A-06X2	存放20层	120	60	460	35-330	5	3.4	10	20	34	34	√	-	√	-	
A-06X3	存放30层	120	60	460	35-330	5	3.4	10	30	34	34	√	-	√	-	
A-06LGX2	铝合金20层	520	60	460	35-330	8	3	10	20	34	34	√	-	√	-	
A-06LGX3	铝合金30层	520	60	460	35-330	8	3	10	30	34	34	√	-	√	-	
A-07X2	存放20层	120	100	460	35-330	5	3.4	10	20	34	34	√	-	-	√	
A-07X3	存放30层	120	100	460	35-330	5	3.4	10	30	34	34	√	-	-	√	
A-07LGX2	铝合金20层	520	520	460	35-330	8	3	10	20	34	34	√	-	-	√	
A-07LGX3	铝合金30层	520	520	460	35-330	8	3	10	30	34	34	√	-	-	√	

外形尺寸: 535*460*570mm		温度℃		存放PCB尺寸		槽型尺寸			插槽数量	基础尺寸		上下面板		齿轮压扣	螺丝固定	重量 kg
产品型号	特点	槽板	环境	插槽长度	可调节宽度mm	槽宽	槽深	间距		A	B	金属	塑料			
A-08	五拼板	120	60	535	50-390	5	3.5	10	50	34	38	√	-	√	-	
A-08S	螺丝调节	120	120	535	50-390	5	3.5	10	50	34	38	√	-	-	√	
A-08LG	铝侧板-齿轮	520	60	535	50-390	8	3	10	50	34	38	√	-	√	-	
A-08SLG	铝侧板-螺丝	520	520	535	50-390	8	3	10	50	34	38	√	-	-	√	

外形尺寸: 535*530*570mm		温度℃		存放PCB尺寸		槽型尺寸			插槽数量	基础尺寸		上下面板		齿轮压扣	螺丝固定	重量 kg
产品型号	特点	槽板	环境	插槽长度	可调节宽度mm	槽宽	槽深	间距		A	B	金属	塑料			
A-09	五拼板	120	60	535	120-460	5	3.5	10	50	34	38	√	-	√	-	
A-09S	螺丝调节	120	120	535	50-460	5	3.5	10	50	34	38	√	-	-	√	
A-09LG	铝侧板-齿轮	520	60	535	120-460	8	3	10	50	34	38	√	-	√	-	
A-09SLG	铝侧板-螺丝	520	520	535	50-460	8	3	10	50	34	38	√	-	-	√	

外形尺寸: 630*530*570mm		温度℃		存放PCB尺寸		槽型尺寸			插槽数量	基础尺寸		上下面板		齿轮压扣	螺丝固定	重量 kg
产品型号	特点	槽板	环境	插槽长度	可调节宽度mm	槽宽	槽深	间距		A	B	金属	塑料			
A-636S	二拼板	120	120	630	50-460	7.1	3.5	10	50	38	38	√	-	-	√	13.1
A-636SLG	铝合金侧板	520	60	535	50-460	7.1	3.5	10	50	38	38	√	-	-	√	

G代表高温、X2X3代表存放20片30片、LG代表铝合金;